



BELL END COLUMN PIPES (PVC)

APPLICATIONS

- Bell end pipe is used for pipeing System
- Pipe for lower pressure water flow applications
- Pipe can handle 140 degrees F in Temp
- Pipe are belled end so no coupling is needed for installation
- Handle low Pressure But has Great Camical Resistance

SALIENT FEATURES

- Non-toxic in every way
- Suitable for depth up to 100 ft to 125 ft
- Available in the range of 1" - 2"
- Easy to carry, handle & install
- Very cost-effective
- High quality finish that ensures unobstructed flow of water.
- NPT threads ensure high tensile load capacity.
- Clear & visible Shakti Hallmark eliminates any possibility of falling prey to spurious PVC pipes.

RANGE

SIZE	TYPE	PRESSURE (KG)	OD (MM)		END THICKNESS (MM)		BARREL THICKNESS (MM)	
1"	MEDIUM	15	32.60	33.20	4.00	4.60	2.00	2.30
1.25"	MEDIUM	15	41.50	42.10	4.50	5.00	2.20	2.40
1.5"	MEDIUM	15	47.50	48.10	4.80	5.30	2.90	3.20
2"	MEDIUM	15	59.50	60.10	5.00	5.50	2.90	3.30

PACKING DETAILS (No's. of Pipes/ Bundle)

Size	3/2.9 Meter	6/5.8 Meter
1"	25	25
1.25"	20	20
1.5"	15	15
2"	10	10

* NPT Thread





uPVC COLUMN PIPES (SS SOCKET)

APPLICATIONS

- Bell end pipe is used for pipeing System
- Pipe for lower pressure water flow applications
- Pipe can handle 140 degrees F in Temp
- Pipe are belled end so no coupling is needed for installation
- Handle low Pressure But has Great Camical Resistance

SALIENT FEATURES

- Non-toxic in every way
- Suitable for depth up to 100 ft to 125 ft
- Available in the range of 1" - 2"
- Easy to carry, handle & install
- Very cost-effective
- High quality finish that ensures unobstructed flow of water.
- NPT threads ensure high tensile load capacity.
- Clear & visible Shakti Hallmark eliminates any possibility of falling prey to spurious PVC pipes.



RANGE

MATERIAL CODE	MATERIAL DISCRIPTION
9000025301	COLUMN PIPE- 32MM (1.25") MED. 15 KG
9000025305	COLUMN PIPE- 40MM (1.50") MED. 15 KG
9000025097	COLUMN PIPE- 50MM (2") MED. 15 KG



PACKING DETAILS (No's. of Pipes/ Bundle)

Size	3/2.9 Meter	6/5.8 Meter
1.25"	20	20
1.5"	15	15
2"	10	10

* NPT Thread

