



# uPVC COLUMN PIPES (SS SOCKET)

## APPLICATIONS

- Bell end pipe is used for piping System
- Pipe for lower pressure water flow applications
- Pipe can handle 140 degrees F in Temp
- Pipe are belled end so no coupling is needed for installation
- Handle low Pressure But has Great Chemical Resistance

## SALIENT FEATURES

- Non-toxic in every way
- Suitable for depth up to 100 ft to 125 ft
- Available in the range of 1.25" - 2"
- Easy to carry, handle & install
- Very cost-effective
- High quality finish that ensures unobstructed flow of water.
- NPT threads ensure high tensile load capacity.
- Clear & visible Shakti Hallmark eliminates any possibility of falling prey to spurious PVC pipes.

## RANGE

MATERIAL CODE	MATERIAL DISCRIPTION
9000025301	COLUMN PIPE- 32MM (1.25") MED. 15 KG
9000025305	COLUMN PIPE- 40MM (1.50") MED. 15 KG
9000025097	COLUMN PIPE- 50MM (2") MED. 15 KG

## PACKING DETAILS (No's. of Pipes/ Bundle)

Size	3/2.9 Meter	6/5.8 Meter
1.25"	20	20
1.5"	15	15
2"	10	10

\* NPT Thread

